


**NEW**



**KURT®**

## 20 SMALL MACHINE TABLE WORKHOLDING OPTIONS

Today's small machines require workholding options to fit smaller tables. KURT has 20 options to fit machine tables measuring **16" and under in the Y dimension**. See table below for all single and double station workholding options.



Model #	Footprint Inches	Hex Length Inches	Max Opening Inches	Max Clamping Force Lbs	Type	# Stations	Jaw Type	Actuation	Notes
SCMX250	2.500 x 5.000	1.110	1.000	1,800	SELF-CENTERING	1	MACHINABLE	MANUAL	
SCMX425	4.000 x 8.000	1.120	2.250	3,000	SELF-CENTERING	1	MACHINABLE	MANUAL	
KTR35	3.500 x 9.188	0.920	4.000	4,500	PULL	1	HARD	MANUAL	
HD4 (AL OR C)	4.000 x 10.000	< 0.125	0.250		DOUBLELOCK	2	MACHINABLE	MANUAL	CUSTOM
MAXLOCK 350	3.50 x 11.463	N/A	3.500	7,000	ANGLOCK	1	HARD	MANUAL	W/STD 8" SCREW
D40	6.380 x 12.340	0.700	3.875	7,807	"D"/PUSH	1	HARD	MANUAL	
3400V	4.000 x 12.644	1.516	6.000	7,500	PULL	1	HARD	MANUAL	
3410V	4.000 x 12.644	1.341	6.000	7,500	PULL	1	HARD	MANUAL	
3620V	6.000 x 12.940	1.940	4.000	6,356	PULL	1	HARD	MANUAL	
3630V	6.000 x 12.940	1.940	4.000	6,356	PULL	1	HARD	MANUAL	
HDM6 (AL OR C)	6.000 x 13.375	0.312	0.250	5,556	DOUBLELOCK	2	MACHINABLE	MANUAL	
HDHM6 (AL OR C)	6.000 x 13.375	0.312	0.250	7,800	DOUBLELOCK	2	MACHINABLE	HYDRAULIC	
3600V-INT	6.000 x 15.060	< 0.125	6.000	6,356	PULL	1	HARD	MANUAL	INTERNAL HEX
3610V-INT	6.000 x 15.060	< 0.125	6.000	6,356	PULL	1	HARD	MANUAL	INTERNAL HEX
3400H-INT	4.000 x 15.224	< 0.125	6.000	7,800	PULL	1	HARD	HYDRAULIC	INTERNAL HEX
3410H-INT	4.000 x 15.224	< 0.125	6.000	7,800	PULL	1	HARD	HYDRAULIC	INTERNAL HEX
3620H-INT	6.000 x 15.350	< 0.125	4.000	12,600	PULL	1	HARD	HYDRAULIC	INTERNAL HEX
3630H-INT	6.000 x 15.350	< 0.125	4.000	12,600	PULL	1	HARD	HYDRAULIC	INTERNAL HEX
MAXLOCK 350	3.500 x 15.463	N/A	7.500	7,000	ANGLOCK	1	HARD	MANUAL	W/OPT 12" SCREW
SCD430-INT	4.000 x 15.500	< 0.125	6.250	4,902	SELF-CENTERING	1	HARD	MANUAL	INTERNAL HEX